





Rundhovedet – A2/A2 - Lukket



**MFX 1261**

Ø d	l (+1/-0,2)	Nitte evne	Beskrivelse	Ø d <sub>k</sub>	k	Ø d <sub>m</sub>	p	Træk (N)	Snit (N)
mm	mm	mm		mm	mm	mm	mm		
<b>3,2</b>	6,0	0,5-1,5	<b>1261 3206</b>	6,0 +/-0,24	≤1,4	~1,90	≥27	2500	2000
(+0,08/-0,10)	8,0	1,5-3,0	<b>1261 3208</b>						
	9,5	3,0-5,0	<b>1261 3209</b>						
Ø3,3	12,0	5,0-7,0	<b>1261 3212</b>						
<b>4,0</b>	6,0	0,5-1,5	<b>1261 4006</b>	8,0 +/-0,29	≤1,7	~2,30	≥27	4000	3000
(+0,08/-0,10)	8,0	1,5-3,0	<b>1261 4008</b>						
	9,5	3,0-5,0	<b>1261 4009</b>						
Ø4,1	12,0	5,0-6,5	<b>1261 4012</b>						
	16,0	6,5-10,5	<b>1261 4016</b>						
<b>4,8</b>	8,0	1,0-3,0	<b>1261 4808</b>	9,5 +/-0,29	≤2,0	~2,90	≥27	5500	4500
(+0,08/-0,10)	9,5	3,0-5,0	<b>1261 4809</b>						
	12,0	5,0-6,5	<b>1261 4812</b>						
Ø4,9	16,0	6,5-10,5	<b>1261 4816</b>						
	20,0	10,5-14,0	<b>1261 4820</b>						