

KLEMBUSWIELEN - SIMPLEX

Voor rollenketting 08B-1

Vlg. Din 8187

1/2" x 5/16"

Tanden aantal	Klembus	Naaf afmeting		Steek cirkel	Kop cirkel	Gewicht ca. kg	Artikel code
		Dm mm	A mm	Dp mm	De mm		
15	1008	45	22	61,80	66,50	0,18	KBW08B-1 15T-H
16	1108	50	22	65,10	69,90	0,19	KBW08B-1 16T-H
17	1210	60	25	69,11	74,50	0,23	KBW08B-1 17T-H
18	1210	60	25	73,14	78,00	0,27	KBW08B-1 18T-H
19	1210	63	25	77,15	82,50	0,28	KBW08B-1 19T-H
20	1610	67	25	81,19	86,00	0,29	KBW08B-1 20T-H
21	1610	71	25	85,21	90,60	0,37	KBW08B-1 21T-H
22	1610	71	25	89,24	94,10	0,38	KBW08B-1 22T-H
23	1610	76	25	93,26	98,70	0,50	KBW08B-1 23T-H
24	1610	76	25	97,29	102,10	0,52	KBW08B-1 24T-H
25	1610	76	25	101,32	106,70	0,57	KBW08B-1 25T-H
26	1610	76	25	105,36	110,20	0,59	KBW08B-1 26T-H
27	1610	76	25	109,40	114,80	0,64	KBW08B-1 27T-H
28	2012	76	32	113,42	118,30	0,67	KBW08B-1 28T-H
29	2012	76	32	117,44	124,80	0,69	KBW08B-1 29T-H
30	2012	90	32	121,49	126,90	0,70	KBW08B-1 30T-H
31	2012	90	32	125,51	131,10	0,71	KBW08B-1 31T-H
32	2012	90	32	129,53	135,30	0,72	KBW08B-1 32T-H
33	2012	90	32	133,55	139,50	0,73	KBW08B-1 33T-H
34	2012	90	32	137,57	143,70	0,74	KBW08B-1 34T-H
35	2012	90	32	141,59	147,90	0,75	KBW08B-1 35T-H
36	2012	90	32	145,61	152,10	0,76	KBW08B-1 36T-H
37	2012	90	32	149,63	156,30	0,77	KBW08B-1 37T-H
38	2012	90	32	153,79	159,20	0,80	KBW08B-1 38T-H
39	2012	90	32	157,81	163,40		KBW08B-1 39T-H
40	2012	90	32	161,83	167,60		KBW08B-1 40T-H
45	2012	100	32	182,07	188,60	1,97	KBW08B-1 45T-H
48	2012	100	32	194,13	201,20		KBW08B-1 48T-H
50	2012	100	32	202,17	209,60		KBW08B-1 50T-H
57	2012	111	32	230,54	237,10	2,70	KBW08B-1 57T-H
60	2012	111	32	242,60	249,70		KBW08B-1 60T-H
76	2012	111	32	307,32	313,90	4,48	KBW08B-1 76T-H
95	2012	111	32	384,11	390,70	6,90	KBW08B-1 95T-H
114	2517	111	44	460,90	467,40	10,00	KBW08B-1 114T-H

Ook afwijkende tandenaantallen op voorraad, specificaties op aanvraag.

Steek	P	= 12,70 mm
Binnenbreedte	E	= 7,75 mm
Roldiameter	D3	= 8,51 mm
Tandbreedte	B1	= 7,20 mm

